



Clear Opening [CO] / Lichte Weite (mm)	-
Percentage of raised pattern / Erhabene Fläche	26,5 %
Outlet Area / Auslassbereich (cm ²)	-
Inlet Area / Einlaufquerschnitt (cm ²)	-

For missing dimensions see 3D data / Fehlende Maße siehe 3D-Datensatz
local article number: 132125

modification: Prüfbubble in Zeichnung ergänzt (Rohteil) / Check dimension bubbles in drawing added	
technical reference: Koetteritzsch, Thorsten	general tolerance: surface: coated (black)
weight: 15.7 kg	document type: production drw.
ACO Tiefbau Vertrieb GmbH Scheidertalstr. 3 65326 Aarbergen www.aco-tiefbau.de	material: see table
created by:	reviewed by:
projection: ISO-E	scale: 1:2

title:
V200 Freestyle class D400
Grating assembled (without slots) "BLIND LEAD-DK"
Rost assembliert (ohne Schlitz) "BLIND LEAD-DK"

The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. Observe copyright by ISO 16014058348

Pos.	Item-No.	Index	Item name	Article number- client 1018	Drw.-No.	Material	Weight (kg)	QTY.
10	1058346	002	Grating coated (without slots) "BLIND LEAD-DK"	1206209	1058346	0.7050 (EN-GJS-500-7)	15.7	1
20	1031196	004	Cast Iron Grate Lock Element	601414	1031196	TPU Shore 65D Schwarz	0.009	2

drawing-no:	index:	release date:	sheet:
16014058348	002	8	1/1